



# TOOLS CHECKLIST

Please make sure you have the items listed below prior to starting the job.

## 1. MATERIALS

- ☐ Visquine (6 mil x 12' W x 100' L roll - placed on top & bottom)
- ☐ 2" tape to hold foam to PCC
- ☐ Foam edge protection (1/4" x 8" W x 100' L roll)
- ☐ Wood or round metal stakes
- ☐ Cold patch (approx. 20 bags or enough to repair base and shoulder)
- ☐ Curing compound
- ☐ 2" x 6" board to form up shoulder if AC is damaged
- ☐ Grease (for thermometer)
- ☐ Replacement pavement markers
- ☐ Plywood or carpet

## 2. TOOLS

- ☐ Rock drill (1 1/2 - 2" depending on size of pin)
- ☐ Round & square point shovels
- ☐ Hudson sprayer (for curing compound)
- ☐ Cleaning brushes
- ☐ Push brooms for traction grooves & clean up
- ☐ Hammer & nails
- ☐ Wheel barrows
- ☐ Utility knife
- ☐ Rubber boots
- ☐ Rubber gloves
- ☐ Single jack to drive pin in
- ☐ Hand or power saw
- ☐ Dust pan
- ☐ Chain

## 3. CONCRETE TOOLS

- ☐ 2' x 4' x 14' aluminum hand screed *or*
- ☐ 2' x 6' x 14' wood hand screed (straight, not bowed)
- ☐ Concrete vibrator
- ☐ Concrete edger trowels
- ☐ 3' to 4' Bull floats with extension poles
- ☐ Flat trowels
- ☐ Concrete thermometer
- ☐ Slab cutter & extractor
- ☐ Concrete saw

## 4. STORM WATER REQUIREMENTS

- ☐ 100 gal. container for containment during clean up
- ☐ 6 mil visquine to line bottom of container
- ☐ Adequate water supply for clean up and all other activities
- ☐ Reading of BMP during tailgate safety meeting
- ☐ Shop Vac to clean up PCC slurry
- ☐ Small trailer for clean out, or two 55 gallon barrels

## 5. EQUIPMENT

- ☐ 14' rolling vibrating screed (if available)
- ☐ Gradall forklift
- ☐ Loader
- ☐ Concrete truck with 4 - 5 slump mix
- ☐ Small roller
- ☐ Vibrator plate
- ☐ Lights (night work)
- ☐ Generator